

2026 Rule Book



*03/02/2026
ITPA*

*2026-2029
Super Stock 4x4*

4x4 Super Stock Rules

1. 6200lb weight class.
2. Truck must have stock frame. Suspension blocks and traction bars will be allowed.
3. Truck body may be different than the frame if approved by the board. Truck frame shall designate make and model of truck. 134-inch wheelbase maximum. Must have full size body.
4. Truck must have OEM production drive train. Dana 70 or smaller front and any rear F106 Rockwell or equal in size. No planetary rear. No drop boxes or reversers. Cut gears allowed in OEM cases.
5. Hydraulic steering is allowed.
6. Rear of block can be no more forward than 12 inches from center of front axle tube.
7. Truck must have all body components: fenders, hood, front doors. Flat beds are **NOT** allowed, tilt front ends allowed, no fiberglass bodies are allowed (except fiberglass hood), no tilt bodies allowed.
8. Maximum 35x12.5 inches DOT stamped tires, no cutting or grooving, no bars, no dual wheels, no chains. Wrangler XT terra tires are allowed. No alterations allowed.
9. Engine must be naturally aspirated. Any single four-barrel carburetor allowed (must be no larger than a 4500 base) with any cast aluminum intake manifold. No sheet metal intake. 550 cubic inches. **Cast iron block, any cast iron heads ONLY.**
10. Open exhaust is allowed and must exit down and back or through upright headers allowed. If running alcohol, headers must exit upright.
11. Weight may be added to the front of the truck; weight or frame may not extend more than 60 inches from the center line of the front axle.
12. No cutting of cabs. If the bed is gutted, it must be covered. Must have inner fender wells or engine side shields (.060 inch thick minimum).
13. Brakes must slide all 4 wheels. Driveline brakes are allowed.
14. Draw bar height is 26 inches for four-wheel drive and must be rigid in all directions. No adjusting hitch height after having height checked.
15. Draw bar length is a minimum of 36% of the wheelbase measured from center line of rear axle to the farthest rear point of hitch opening. Must not exceed more than 12 inches from body.
16. Front gas tank is no more than 60 inches from the center of the front axle.
17. After you cross the scales, no weight or fuel is to be added. If a truck makes multiple hooks, then fuel can be added after the first hook if necessary.
18. No air or hydraulic hoses attached to any part of the front suspensions.
19. Pony motor allowed for electrical charging purposes only.
20. All General Rules Apply.